

Compact urban ability

The F3 Corpus compact size and agility allows users to easily maneuver in and out of tight spaces. The *Smooth* suspension always ensures a comfortable ride in urban areas.

Corpus - follows the contours of the body

The Corpus seating system features an ergonomic design that follows the contours of the body. Improved comfort, pelvic positioning, lateral stability and immersion are all key objectives of the new Corpus cushions.

Corpus cushions feature softer dual-density foam on the backrest, a re-designed pelvic well and Stretch-Air™, a breathable, water-resistant cushion fabric that is machine-washable at 60°C.

Active Reach

Tilts the seat forward by up to 30° and raises it to extend functional reach, aid in transfers and your daily activities.

Active Height

Enables you to drive up to 5 km/h while fully elevated and combines seamlessly with *Active Reach* to give you the ultimate advantage in accessing your environment.

Power recline

Smooth and safe power recline with seamless sheer reduction for any user up to 150kg.


More drivability

The new Permobil battery and Permobil VoltPro charger work together to provide you with a greater driving distance, optimized charging times and longer battery life.

Safer driving after dark

Optional LED lights front and back for improved brightness and visibility.





F3 Corpus® Specifications

Max. speed	6/8/10 km/h
Range (G34: 65 Ah / G24: 85 Ah batteries)	30-40 km*
Max. user weight	150 kg
Obstacle climbing	60 / 75 mm
Min. turning diameter	1350 mm
Turning in corridor	1040 mm
Suspension	Independent on all wheels
Electronics R-net	120 A
Width incl. seat	610-790 mm
Height	970–1170 mm
Min. transport length excl. / incl. Anti-tippers	790/890 mm
Min. transport height (folded backrest)	825 mm
Weight incl. batteries 65/85 Ah	173,0/185,6 kg
Weight of batteries 65/85 Ah	2x17,5/2x23,8 kg
Seat height (with electric seat elevator)	450-750 mm
Seat depth	370-570 mm (by 25 mm)
Seat width	420-570 mm (by 50 mm)
Backrest width	360/410/460/510 mm
Backrest height	470, 545-670 mm (by 25 mm)
Distance between armrests	380-480/480-580 mm
Crash tested ISO 7176-19 - docking system	Yes – max 136 kg user weight
Crash test ISO 7176-19 - straps / tie-down	Yes – max 150 kg user weight
Tested according to EN12182/EN12184 CE	Yes









VIOLET

















915-1015 mm



Seat elevator
Active Height 0-300 mm



Anterior tilt

Active Reach* 5-30°
20° and 30° require
VS legrest



Power and manual leg rest 90–180°



Power backrest **85–180°** Manual backrest **120°**

610 mm



Posterior tilt 0-50°





